

Tapping Devices for Single Valve Kegs

Coupling Head D&S Style Valves:

- KAM-Loc Keg lock feature ends unexpected spray of beer or loss of gas...guided Kam-Loc arm prevents the tap from being removed from keg with the probe in the tapped position. The next keg cannot be tapped with the probe in the “down” or “tapped” position.
- Forged brass body has male beer thread pressure inlet; by removing hex nut, nipple, and check valve assembly tap can be used for series tapping.
- Probe check valve retainer is easily removable for cleaning and also acts as a beer line washer.
- Built-in pressure line shut-off prevents loss of gas when the keg is untapped.
- Integral non-adjustable safety (set at 55-65 PSIG) protects kegs against accidental over-pressurization.
- Safety has easy to use manual bleed-off; improper applied pressure conditions can be corrected.
- Available for U.S. or European Single Valve Keg.



CH5000-45L

“New & Improved”
Now with probe washer & redesigned
body/handle stop

Model Numbers	Description
CH5000-45	Lever Tap for US Kegs
CH5000-45L	Lever Tap with Kam-Loc barrel for US kegs w/locking leg
CH5100L	Lever Tap with Kam-Loc Barrel Lock for European Kegs

Replacement Parts

Part Number	Description
1. 80219	Retainer, Ball
2. 80220	Ball, Coupler
3. 80222-01	Probe, Coupler Nkl Pltd
4. 80231	O-Ring, Coupler, Probe
5. FT40-15	Washer, Probe Molded
6. 80218-01	Handle Assy, Coupler White
7. 80217	Body, Coupler Nkl Pltd w/stop
8. 24253	Seal, Bottom Bronco
9. 80226	Stem, Coupler
10. 70510	Seal, beer-010 Quad-Ring
11. 24278	Retainer, Prv
12. 70530	Spacer, Safety
13. 24214	Spring, Low Pressure 60 psi
14. 80230	Ring, Coupler Split
15. 80225	Pin, Coupler Hinge
16. 80221	Valve, Check-Coupler
17. 80227	Nipple, Coupler Hose
18. 80228	Hex Nut (Not Shown)

