



NOTES:

1. INLET: CO2 FITTING WITH CGA 320 NUT
2. OUTLETS: 1/4" FLARE W/CHECK
3. GAUGES: 160# AND 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI.
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: POLY, BLUE
7. UL252: SERIES 5740

MATERIAL	NAME	DATE
	DRAWN EG	06/11/10
FINISH	ENG APPR.	PF
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE: **REG. PRI SODA, 160#, TNK FTG, 1/4F-CV OUT, 2000#, POLY BONNET, BLUE**

SIZE	DWG. NO.	REV
A	T5741PMHPB_SALES	B

SCALE: 1:4	DO NOT SCALE DRAWING	SHEET 1 OF 1
------------	----------------------	---------------------