



NOTES:

1. INLET: NITROGEN TANK FITTING W/ NUT
2. OUTLET: 5/16" BARB SHUTOFF WITH CHECK
3. GAUGES: 160# AND 3000#
4. SAFETY BLOW-OFF 130 ± 4 PSI.
5. WORKING PRESSURE: 0-120 PSI
6. BONNET: ZINC, BLACK

MATERIAL	NAME	DATE
	DRAWN	JPK 08/02/11
FINISH	ENG APPR.	
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE:		
REG, PRI, NI, 0-120, 160#, NI FTG, 5/16-CV SHUTOFF, 3000#, BLK BONT		
SIZE	DWG. NO.	REV
A	5741PMHPNT_SALES	A
SCALE: 1:2	DO NOT SCALE DRAWING	SHEET 1 OF 1