



**NOTES:**

1. INLET: CO2 FITTING W/CGA 320 NUT
2. OUTLETS: 5/16" & 1/4" BARB SHUTOFFS WITH BALL-CHECK
3. GAUGES: 60#, 160#, 2000#
4. SAFETY BLOW-OFF: 60 ± 5 / 130 ± 4 PSI
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: POLY, GRAY/RED CAPS

MATERIAL	NAME	DATE	 <small>2348 NORTHWESTERN DR. SAN ANTONIO, TX 78248</small>
	DRAWN	LG	
FINISH	ENG APPR.		TITLE:
	<p align="center"><b>PROPRIETARY AND CONFIDENTIAL</b></p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.</p>		<p><b>REG, HYB, 2P2P, 60/160, TNK, 5/16B-CV SHTF+1/4B-CV SHTF, 2K, GRY/RD</b></p>
DIMENSIONS ARE IN INCHES			SIZE DWG. NO.
TOLERANCES:			<b>A</b> T5752HP-05-SALES
FRACTIONAL ± 1/64			REV
ANGULAR: MACH ± 1/2°			<b>A</b>
BEND ±			SCALE: 1:4
TWO PLACE DECIMAL ± 0.015			DO NOT SCALE DRAWING
THREE PLACE DECIMAL ± 0.005			<b>SHEET 1 OF 1</b>