



NOTES:

1. INLET: CO2 FITTING WITH CGA 320 NUT
2. OUTLETS: 1/4" FLARE WITH CHECK
3. GAUGES: 160# (2 EA), 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: SMALL ZINC, BLACK
7. UL252: SERIES 3740

MATERIAL	NAME	DATE
	DRAWN JPK	05/04/10
FINISH	ENG APPR.	P.F. 06/14/10
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE: **REG, PRI, SODA, 2P2P, 160#, TNK FTG, 1/4F-CV OUT, 2000#, SM BLACK BONT**

SIZE	DWG. NO.	REV
A	3752_SALES	C
SCALE: 1:2	DO NOT SCALE DRAWING	SHEET 1 OF 1